

IN THE CLAIMS

Please amend the claims as follows:

1 (Currently Amended). An ultrasonic probe for insertion into an endocavity of a specimen in order to examine ~~examining a~~ the specimen, comprising:

a holding portion including a first housing portion;

an insertion member configured to move along the first housing portion, the insertion member having at least one end for insertion into ~~an~~ the endocavity of the specimen; and

an ultrasonic generator provided at the one end of the insertion member and configured to transmit an ultrasound pulse to the specimen and collect an echo signal resulting from the transmitted ultrasound pulse,

wherein the holding portion is coupled to the ultrasonic generator so that a position of the ultrasonic generator is adjustable in accordance with an angle of the holding portion.

2 (Original). The ultrasonic probe according to claim 1, wherein the insertion member moves through the first housing portion.

3 (Original). The ultrasonic probe according to claim 1, wherein the first housing portion includes an insertion member stopping portion configured to prevent the insertion member from moving through the holding portion.

4 (Original). The ultrasonic probe according to claim 1, further comprising a first fixer disposed at the holding portion, the first fixer being configured to keep the insertion member and the holding portion at a predetermined position relative to each other.

5 (Original). The ultrasonic probe according to claim 4, wherein the insertion member includes a plurality of first projections around a surface of the insertion member along a longitudinal direction of the insertion member and the holding portion includes a second projection configured to engage one of the plurality of first projections, and wherein the first fixer keeps the engagement.

6 (Original). The ultrasonic probe according to claim 1, wherein the insertion member includes a relay member having a second housing portion and an insertion end member having the one end, the relay member being configured to move along the first housing portion, the insertion end member being configured to move along the second housing portion.

7 (Original). The ultrasonic probe according to claim 6, further comprising a first fixer disposed at the holding portion and a second fixer disposed at the relay member, the first fixer being configured to keep the relay member and the holding portion at a first predetermined position relative to each other, the second fixer being configured to keep the insertion end member and the relay member at a second predetermined position relative to each other.

8 (Original). The ultrasonic probe according to claim 6, wherein the first housing portion includes a relay member stopping portion configured to prevent the relay member from moving through the holding portion, and wherein the second housing portion includes an insertion end member stopping portion configured to prevent the insertion end member from moving through the relay member.

9 (Original). The ultrasonic probe according to claim 7, wherein the relay member includes a plurality of first projections around a surface of the relay member along a longitudinal direction of the relay member and the holding portion includes a second projection which is engaged with one of the plurality of first projections, and wherein the first fixer fixes the engagement.

10 (Original). The ultrasonic probe according to claim 7, wherein the insertion end member includes a plurality of first projections around a surface of the insertion end member along a longitudinal direction of the insertion end member and the relay member includes a second projection which is engaged with one of the plurality of first projections, and wherein the second fixer fixes the engagement.

11 (Currently Amended). An ultrasound imaging apparatus for obtaining and displaying an ultrasound image, the apparatus comprising:

an ultrasonic probe for insertion into an endocavity of a specimen in order to examine
~~examining a~~ the specimen, including [[:]]

a holding portion including a first housing portion, [[:]]

an insertion member configured to move along the first housing portion, the insertion member having at least one end for insertion into [[an]] the endocavity of the specimen, [[:]] and

an ultrasonic generator provided at the one end of the insertion member and configured to transmit an ultrasound pulse to the specimen and collect an echo signal resulting from the transmitted ultrasound pulse,

wherein the holding portion is coupled to the ultrasonic generator so that a position of the ultrasonic generator is adjustable in accordance with an angle of the holding member; and
a display coupled to the ultrasonic probe and configured to display the ultrasound image based on the echo signal.

12 (Currently Amended). A method of ~~providing~~ generating an ultrasound image, comprising:

providing a holding portion having a housing portion;
providing an insertion member having a distal end and a proximal end, the distal end having an ultrasonic generator; ~~and~~

adjusting a position of the ultrasonic generator, which is coupled to the holding portion, in accordance with an angle of the holding portion;

slidably coupling the insertion member to the housing portion of the holding portion;
inserting the distal end of the insertion member into an endocavity of a specimen; and
generating the ultrasound image.

13 (Canceled).